

Repair Instructions

Replacing and Installing a Rubber Foot.

Elite Models that Apply: Elite Grand 4, 5, and 5-LE.

Step	Description	Tools	Picture
1	<p>If the rubber foot came off, but the screw is still attached to the platform (and not bent out of shape), then you should be able to remove the old rubber foot, and screw on the new foot by hand. If the screw is bent, or broken, then you will need to remove the platform to install the new screw and rubber foot.</p>		
2	<p style="text-align: center;">Removing The Case</p> <p>Step 1.) Unscrew the (6) Phillips-head screws along the bottom of the red case where it attaches to the chassis of the machine. (2-front, 2-rear, one on each side)</p> <p>Step 3.) Lift the red case off the chassis and set it aside.</p>	Phillips Screw Driver	 <p style="text-align: center;">Case Screws (Front & Rear)</p>  <p style="text-align: center;">Case Screws (Side)</p>  <p style="text-align: center;">Case Removed</p>
3	<p style="text-align: center;">Removing The Platform</p> <p>Step 1.) Using a 9/16" crescent wrench, and a 9/16" wrench, unscrew the bolt in the center of the Platform which is holding the Platform to the bottom of the machine.</p> <p>Step 2.) With the Platform detached, position it so that the 4 rubber feet are touching the ground, and the white plastic spacer is pointing up.</p>	Phillips Screw Driver 9/16" Crescent Wrench 9/16" Wrench	 <p style="text-align: center;">Platform with Nut removed.</p>  <p style="text-align: center;">Platform being removed from Chassis.</p>

Repair Instructions



Replacing and Installing a Rubber Foot.

	<p style="text-align: center;">Installing the Rubber feet</p> <p>Step 1.) Unscrew the rubber foot or feet that need to be replaced. Using a hammer, tap on the screw that is broken or bent until it pops out.</p> <p>Step 2.) Place the screw through the hole so that the threading is pointed up like the rubber feet.</p> <p>Step 3.) Fasten the new rubber feet to the newly inserted screw and rotate clockwise until the foot is tight.</p>	<p>Ham-mer</p> <p>Phillips Screw Driver</p>	<p>Foot being fastened to platform.</p> <p>Rubber feet installed on platform.</p>
	<p style="text-align: center;">Re-attaching the Platform the Chassis</p> <p>Step 1.) Carefully line up the platform with the Chassis, so that the Rack Gear teeth, fit in-between the Spur Gear teeth. (See picture below).</p> <p>Step 2.) Push the 1/2 inch platform bolt thru the bottom of the platform, so that the threaded edge is popping out of the top/middle of the chassis.</p> <p>Step 3.) Put the Battery Negative Ground Loop over the threads of the 1/2 inch platform bolt, and cap it off with the bolt.</p> <p>Step 4.) Tighten the nut and yoke bolt until the nut can be turned by your thumb and index finger.</p>	<p>Phillips Screw Driver</p> <p>9/16" Crescent Wrench</p> <p>9/16" Wrench</p>	<p>Rack Gear teeth lining up with Spur Gear teeth.</p> <p>The threading is pointed out in blue, and the Battery negative Ground Loop is orange.</p>

Repair Instructions

Replacing and Installing a Rubber Foot.

	<p><i>*If the platform bolt is tightened too much, this can cause a Feedback or Overcurrent Sweep Motor Error.</i></p>		
	<p style="text-align: center;">Re-attaching The Case</p> <p>Step 1.) Lift the red case and lower until it is covering the whole Chassis of the machine.</p> <p>Step 2.) Screw the (6) Philips-head screws along the bottom of the red case where it attaches to the chassis of the machine. (2-front, 2-rear, one on each side)</p>	<p>Phillips Screw Driver</p>	 <p>Case Removed</p>  <p>Case Screws (Front & Rear)</p>  <p>Case Screws (Side)</p>
	<p>Contact Lobster Sports Support at 1-800-526-4041 ext.14 If you have any questions or you need to order a replacement foot contact Lobster Sports Support at 1-800-526-4041 ext.1003.</p>		

How to Order Elite Replacement Parts	Elite Parts
<p>Website: http://www.lobstersports.com Email: sales@lobstersports.com Phone: 800.526.4041 Fax: 818.764.6061 We accept Visa, MasterCard or Discover & PayPal</p>	<p>For All models of Lobster Tennis and Pickleball machines: EAF3 Rubber Foot</p>